

VT 547 BIOMEDICAL CHEST FREEZER

-40°C -60°c

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.





0. t Di i U U D	000-000-000	
Outer Dimensions HxWxD, mm	932x1664x66	
Inner Dimensions HxWxD, mm	670x1500x50	
Weight Gross/Net, kg	92,4/10	
Material inner cabinet	Painted Ste	
Material outer cabinet	Painted Ste	
Packaging weight, kg		
Packaging dimensions HxWxD, mm		
Insulation thickness, mm		
Insulation type	Polyurethane with Cyclopentar	
Mobility / Castors	Ye	
Refrigerant, Type	Nature	
Number of compressors		
Internal Air Distribution	Stat	
Number of Probes		
CONTROLLER		
Controller	XR30C	
Controller language	No language - only 3 dig	
USB Connection		
Logging	N	
Temperature Graph		
High/Low Temp. Alarm	Ye	
Open Door Alarm	N	
Probe Failure Alarm	Ye	
Power Failure Alarm	N	
STORAGE		
Volume, Gross/net, L	49	
Baskets		
Basket material	Steel coated with plastic powde	
Innerlids	Λ	
FEATURES		
Lock	Ye	
LED Light	N	
Battery Backup for Controller, 24h	Λ	
Porthole	Yes - Ø 12 mi	
Dry Contact	N	
Door	Sol	
Door Reversibility	N _i	



BIOMEDICAL

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.

Frequency	Hz	50Hz
Max Ambient	°C	30°C
Max Humidity	% rh	55%
PERFORMANCE		
All data in RT20°C		
Temperature Range	°C	-40 to -60
Uniformity in performance - difference +/- from Avg set point	°C	4,8
Pull down time (from 25 to factory setpoint)	Minutes	176
Hold over time (from factory SP to -25, -40 and -60) Empty	Minutes	76-81
Refrigerant		Nature R
Number of probes	pcs	1
Defrost	y/n	No
Internal air distribution		Static
Number of compressors	pcs	1
Safety thermostat	y/n	No
Energy 24 hours	kWh/24h	5,775
Energy year	kWh/year	2107,875